

# TOPGUN 200 LCD

## Specifications

Input Voltage (V)	240 A/C
Frequency (Hz)	50/60 Hz
Output Current Range (A)	10 -200 A MIG
Rated Duty Cycle (%)	30% @ 200A
	60% @ 165A
	100% @ 130A
Machine Weight	15.5 Kg
Machine Dimensions(mm)	510x210x380
Package weight	23 Kg
Package Dimensions	520x350x390
Warranty	3 Years



## Package Includes

Users Manual Fitted 15A Plug  
 4 MTR MB24 Euro-Fit Mig Torch  
 4 MTR Electrode Holder  
 4 MTR Earth Lead  
 0.8mm-0.9mm "V" smooth roller  
 0.9mm-1.2mm "F" knurled roller

Regulator -Argon

TGRRARG










## Ordering Information

Topgun 200 LCD TGWMIG200LCD

## Optional Extras

Tig 17 Torch TGT17V435

# 3 YEAR WARRANTY

INVERTER DC MIG WELDER							
POWER MIG 200 LCD							
PART NO.				STANDARD		EN60974-1:2012	
1~ 				U <sub>i</sub> =110V			
 --- ---	25A/15.3V-140A/21V			U <sub>0</sub> =67V			
	X	40%	60%	100%	I <sub>1max</sub> =37A		
	I <sub>2</sub>	140A	115A	90A	I <sub>1eff</sub> =23.4A		
	U <sub>2</sub>	21V	19.8V	18.5V			
 --- ---	10A/10.4V-140A/15.6V			U <sub>0</sub> =14V			
	X	40%	60%	100%	I <sub>1max</sub> =28A		
	I <sub>2</sub>	140A	115A	90A	I <sub>1eff</sub> =17.7A		
	U <sub>2</sub>	15.6V	14.6V	13.6V			
 --- ---	10A/20.4V-100A/24V			U <sub>0</sub> =14V			
	X	40%	60%	100%	I <sub>1max</sub> =28A		
	I <sub>2</sub>	100A	85A	65A	I <sub>1eff</sub> =17.7A		
	U <sub>2</sub>	24V	23.4V	22.6V			
1~ 				U <sub>i</sub> =230V			
 --- ---	25A/15.3V-200A/24V			U <sub>0</sub> =67V			
	X	40%	60%	100%	I <sub>1max</sub> =28A		
	I <sub>2</sub>	200A	165A	130A	I <sub>1eff</sub> =17.7A		
	U <sub>2</sub>	24V	22.3V	20.5V			
 --- ---	10A/10.4V-200A/18V			U <sub>0</sub> =14V			
	X	40%	60%	100%	I <sub>1max</sub> =22A		
	I <sub>2</sub>	200A	165A	130A	I <sub>1eff</sub> =13.9A		
	U <sub>2</sub>	18V	16.6V	15.2V			
 --- ---	10A/20.4V-200A/28V			U <sub>0</sub> =14V			
	X	40%	60%	100%	I <sub>1max</sub> =32A		
	I <sub>2</sub>	200A	165A	130A	I <sub>1eff</sub> =20.2A		
	U <sub>2</sub>	28V	26.6V	25.2V			
		1~50-60Hz		IP23		H AF 15.5kg	